

# Highly versatile board for structural use in load bearing dry or humid conditions.

SterlingOSB® 3

- Uniform, high quality panels
- No knots, voids or de-laminating problems
- Stronger and tougher than most softwood plywood
- Easy to work with
- Nails can be driven as close as 8mm from panel edge without splitting
- Can be sanded or un-sanded
- Can be finished with most popular surface treatments

- Use in dry conditions**
- DIY projects
  - Garden sheds
  - Packaging and pallets
  - Shelving/Boxing in
  - Internal hoarding
  - Exhibition displays
  - Built-in furniture
  - Interior decorative

- Use in humid conditions**
- Site hoardings
  - Agricultural buildings
  - Caravans
  - Portable buildings
  - Flooring
  - Wall sheathing
  - Flat and pitched roofs
  - Timber frame



## SterlingOSB 3 is available\* in

Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
9, 11, 15, 18	2400	1200	SE	100, 82, 60, 50
9, 11, 15, 18	2440	1220	SE	100, 82, 60, 50
9	2700	1200	SE	100

\*Minimum quantities and lead times may apply

## Our SterlingOSB range - a versatile range designed for purpose

- SterlingOSB 3
- SterlingOSB 3 T&G
- SterlingOSB StrongFix
- SterlingOSB SiteCoat
- SterlingOSB Fire Solutions

SterlingOSB conforms with:



For more information on SterlingOSB, call 01786 819 225 or if you require technical advice call: 01463 792 424

[SterlingOSB.com](http://SterlingOSB.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

**SterlingOSB®**  
Strength you can build on

## Tongue and groove board with a sanded surface finish, for speedy installation.

- T&G profile helps elongate lifespan of boards by reducing movement
- Sanded and machined to exact tolerances
- Sanded surface designed to offer excellent finish with most surface treatments
- No knots, voids or de-laminating problems
- Stronger and tougher than most softwood plywood
- Fully BBA approved

Use in humid conditions

- Flooring
- Flat and pitched roofs
- Timber frame

It performs in humid conditions, making it ideal for house building and construction.



### SterlingOSB 3 T&G is available\* in

Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
18, 22	2400	1200	TG2	50, 40
18, 22	2440	1220	TG2	50, 40
18	2400	590	TG4	100
18	2440	590	TG4	100

\*Minimum quantities and lead times may apply

### Our SterlingOSB range - a versatile range designed for purpose

- SterlingOSB 3
- SterlingOSB 3 T&G
- SterlingOSB StrongFix
- SterlingOSB SiteCoat
- SterlingOSB Fire Solutions

SterlingOSB conforms with:



The mark of responsible forestry

For more information on SterlingOSB, call 01786 819 225  
or if you require technical advice call: 01463 792 424

[SterlingOSB.com](http://SterlingOSB.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

 **SterlingOSB®**  
Strength you can build on

SterlingOSB StrongFix is simple to fit, highly versatile and ideal for fixing cabinets, radiators, wash basins, railings etc to stud walls.

- Precision machined SterlingOSB 3 to fit standard metal C-stud frames with 600mm centres
- Provides a strong fixing point for fixtures and fittings up to 400kg anywhere on the panel
- All the inherent benefits of SterlingOSB 3 – no knots or voids
- Meets BS5234-2 requirements
- Ideal for fixing cabinets, radiators, wash basins, railings etc to stud walls

Use in **humid** conditions  Dry lining



SterlingOSB StrongFix is available\* in

Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
18	2400 <sup>†</sup>	597 <sup>†</sup>	SE	50

\*Minimum quantities and lead times may apply. <sup>†</sup> Other sizes are available on request

Our SterlingOSB range - a versatile range designed for purpose

- SterlingOSB 3
- SterlingOSB 3 T&G
- SterlingOSB StrongFix
- SterlingOSB SiteCoat
- SterlingOSB Fire Solutions

SterlingOSB conforms with:



For more information on SterlingOSB, call 01786 819 225  
or if you require technical advice call: 01463 792 424

[SterlingOSB.com](http://SterlingOSB.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

**SterlingOSB®**  
Strength you can build on

# SterlingOSB® SiteCoat

WE MAKE IT BETTER  
ACROSS THE BOARD

Filled and primer coated on one side,\*\*  
ready for paint or site graphics.

- For the application of logos and other marketing info on site hoardings
- Standard fixing and woodworking methods
- Factory primed white or with a choice of colour\*
- Easy and economical
- Improved durability over untreated plywood or OSB
- Eco-friendly, non-solvent coating
- Fully BBA approved

- Use in **humid** conditions
- Site hoardings
  - Fencing

SiteCoat is readily coated and filled on one side\*\* with a non-solvent coating - meaning less work when you want to paint or graphic your site hoarding.

SterlingOSB SiteCoat is available\* in

Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
18	2440	1220	SE	50

\*Minimum quantities and lead times may apply

\*\*Two sided coated product is available depending on a minimum order quantity



Our SterlingOSB range - a versatile range designed for purpose

- SterlingOSB 3
- SterlingOSB 3 T&G
- SterlingOSB StrongFix
- SterlingOSB SiteCoat
- SterlingOSB Fire Solutions

SterlingOSB conforms with:



For more information on SterlingOSB, call 01786 819 225  
or if you require technical advice call: 01463 792 424

[SterlingOSB.com](http://SterlingOSB.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

 **SterlingOSB®**  
Strength you can build on

\*Minimum order quantity applies to colour choice other than white

Join in the conversation, #SterlingOSB  @Sterling\_OSB  SterlingOSB

# SterlingOSB® Fire Solutions

WE MAKE IT BETTER  
ACROSS THE BOARD

Developed specifically in response to the STA (Structural Timber Association) published guidelines to reduce fire spread during the construction phase.

- Fully compliant with the Building Regulation fire protection requirements\* to match the generic categories of timber frame in STA published guidelines
- Reduce potential radiant heat emissions to reduce the risk of fire spread to neighbouring buildings during construction
- All the inherent benefits of SterlingOSB 3
- 15mm with intumescent coating on both sides of the panel
- Suitable for FR Build decking

Use in humid conditions  Timber frame

The purpose of the Structural Timber Association guidelines is to reduce potential radiant heat emissions to acceptable levels.



SterlingOSB Fire Solutions is available\*\* in

	Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
FS-300	15	2400	1200	SE	60

\*\*Minimum quantities and lead times may apply

Our SterlingOSB range - a versatile range designed for purpose

- SterlingOSB 3
- SterlingOSB 3 T&G
- SterlingOSB StrongFix
- SterlingOSB SiteCoat
- SterlingOSB Fire Solutions

SterlingOSB conforms with:



For more information on SterlingOSB, call 01786 819 225  
or if you require technical advice call: 01463 792 424

[SterlingOSB.com](http://SterlingOSB.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

**SterlingOSB®**  
Strength you can build on

\*When used in conjunction with insulation

Join in the conversation, #SterlingOSB @Sterling\_OSB SterlingOSB

# High-strength P5 wood particleboard for domestic and most other floors.

- Square-edged or tongue and groove profile
- Stable, durable, and easy to lay
- Moisture-resistant
- Strong and robust flooring
- Provides an excellent surface for subsequent floor laying operations
- Removes the need for intermediate noggins

- Suitable for
- Dry domestic
  - Domestic new build
  - Refurbishment
  - Commercial\*

CaberFloor P5 is a high-strength wood particleboard engineered for all domestic and most other floors.

\* Suitable for commercial use in 22mm only

## CaberFloor P5 is available\*\* in

Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
18	2400	600	TG4	80
22	2400	600	TG4	66

\*\*Minimum quantities and lead times may apply



## Our CaberBoard range - flooring systems for domestic and commercial floors

- |                   |                        |                         |
|-------------------|------------------------|-------------------------|
| • CaberFloor P5   | <b>Adhesives</b>       | <b>Tapes</b>            |
| • CaberDek        | • CaberFix D4          | • CaberFix Tape         |
| • CaberShieldPlus | • CaberFix D3          | • CaberFix X-Treme Tape |
| • CaberAcoustic   | • CaberFix Joint&Joist |                         |

CaberFloor P5 conforms with:



For more information on CaberBoard, call 01786 819 225 or if you require technical advice call: 01786 819 449

[CaberBoard.com](http://CaberBoard.com)

# P5 grade flooring, protected from the elements and constructions mess with a strong, waterproof and slip-resistant peelable film.

- A strong waterproof and slip resistant peelable film bonded to the top surface
- Impact, puncture and tear resistant film withstands high site traffic
- BBA approved for 42 days exposure\* when installed with CaberFix
- 44db sound reduction when used in conjunction with leading I-beam and insulation manufacturers
- Complies with BS EN312: part 5

Suitable for

- Dry domestic
- Domestic new build
- Refurbishment
- Commercial†
- Clean finish in exposed conditions
- Exposed construction phase

The UK's market leading particleboard flooring with a tough, waterproof and slip-resistant film



† Suitable for commercial use in 22mm only. \* When installed according to manufacturer's instructions

## CaberDek is available\*\* in

Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
18	2400	600	TG4	80
22	2400	600	TG4	66

\*\*Minimum quantities and lead times may apply

## Our CaberBoard range - flooring systems for domestic and commercial floors

- |                   |                        |                         |
|-------------------|------------------------|-------------------------|
| • CaberFloor P5   | <b>Adhesives</b>       | <b>Tapes</b>            |
| • CaberDek        | • CaberFix D4          | • CaberFix Tape         |
| • CaberShieldPlus | • CaberFix D3          | • CaberFix X-Treme Tape |
| • CaberAcoustic   | • CaberFix Joint&Joist |                         |

CaberDek conforms with:



For more information on CaberBoard, call 01786 819 225 or if you require technical advice call: 01786 819 449

[CaberBoard.com](http://CaberBoard.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

**CaberBoard**<sup>®</sup>  
Trusted flooring systems

## An advanced product designed to keep you building in all weathers.

- Double-sided protection with a tough, permanent waterproof coating
- BBA approved for 42 days exposure\* when used with CaberFix D4 adhesive
- Non-slip safe working platform that withstands high site traffic
- Easy to slide into place with smooth underside
- Colour coded sides to make it easy to identify top surface
- All the inherent benefits of CaberFloor P5

Suitable for

- Dry domestic
- Domestic new build
- Refurbishment
- Commercial†
- Exposed construction phase

CaberShieldPlus used with CaberFix D4 is designed to keep you building in the unpredictable British weather



† Suitable for commercial use in 22mm only. \* When installed according to manufacturer's instructions

### CaberShieldPlus is available\*\* in

Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
18	2400	600	TG4	80
22	2400	600	TG4	66

\*\*Minimum quantities and lead times may apply

### Our CaberBoard range - flooring systems for domestic and commercial floors

- |                   |                        |                         |
|-------------------|------------------------|-------------------------|
| • CaberFloor P5   | <b>Adhesives</b>       | <b>Tapes</b>            |
| • CaberDek        | • CaberFix D4          | • CaberFix Tape         |
| • CaberShieldPlus | • CaberFix D3          | • CaberFix X-Treme Tape |
| • CaberAcoustic   | • CaberFix Joint&Joist |                         |

CaberShieldPlus conforms with:



For more information on CaberBoard, call 01786 819 225 or if you require technical advice call: 01786 819 449

[CaberBoard.com](http://CaberBoard.com)



# CaberFloor P5 with an acoustic layer to reduce both impact and airborne transmitted sound.

- Available as 18mm or 22mm CaberFloor P5 with 10mm sound reducing layer
- Reduces impact sounds transmission by  $\Delta L_w$  19dB\*
- Contributes to airborne noise reduction†
- Use CaberFix D3 adhesive in the joints
- To be overlaid onto an existing deck
- Use in conjunction with flanking strip
- Made in the UK using eco recycled felt

- Suitable for
- Dry domestic
  - Domestic new build
  - Refurbishment
  - Commercial\*\*



\*19dB sound reduction applies when CaberAcoustic is installed on its own. Greater reductions applicable (see table) when used within a system for noise transference reduction.

† When used in the right system.

\*\* Suitable for commercial use in 22mm only

## CaberAcoustic is available\*\* in

Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
28***	2400	600	TG4	40
32***	2400	600	TG4	36

\*\*Minimum quantities and lead times may apply. \*\*\*Including 10mm acoustic layer

## CaberAcoustic performance

	28mm†	32mm††
Impact $L'_{nT,w}$ dB	54	52
Airborne $D_{nT,w}$ dB	60	58
Airborne $D_{nT,w} + C_{tr}$ dB	54	53

## Our CaberBoard range - flooring systems for domestic and commercial floors

- |                   |                        |                         |
|-------------------|------------------------|-------------------------|
| • CaberFloor P5   | <b>Adhesives</b>       | <b>Tapes</b>            |
| • CaberDek        | • CaberFix D4          | • CaberFix Tape         |
| • CaberShieldPlus | • CaberFix D3          | • CaberFix X-Treme Tape |
| • CaberAcoustic   | • CaberFix Joint&Joist |                         |

CaberAcoustic conforms with:



For more information on CaberBoard, call 01786 819 225 or if you require technical advice call: 01786 819 449

[CaberBoard.com](http://CaberBoard.com)

## A range of adhesives specifically developed for use with CaberBoard flooring.

### CaberFix® D4

A one-bottle adhesive and sealing solution that provides BBA approval\* on CaberDek and CaberShieldPlus.

- Bonds T&G joints, flooring to joists, and seals exposed perimeter and edges
- Full BBA approval for 42 days exposure when installed according to manufacturer's instructions
- Solvent-free, one-component polyurethane adhesive
- Foaming adhesive can be seen in the joints making sure a seal is made
- Easy to use, easy to hold 1kg bottle with easy flow nozzle
- Meets BS EN 204/D4

\*When installed according to manufacturer's instructions

### CaberFix® D3

Powerful, water resistant D3 glue designed for sealing and fixing tongue and groove flooring.

- Fast-setting, it forms a strong, hard and rigid glue line
- D3 PVA has superior properties over standard PVA glues
- No fillers required
- Full BBA approval for 42 days exposure when installed according to manufacturer's instructions
- Conforms to DIN EN 204 D3 and BS 476 part 6
- Use with CaberFloor P5, CaberDek and CaberAcoustic

### CaberFix® Joint&Joist

A fast-setting, strong PU adhesive and sealant designed for use with CaberBoard flooring.

- Provides a strong, silent bonding layer between floor and joists
- Creates a waterproof seal in T&G joints
- Bonds in damp conditions to a variety of materials
- Fast-setting and easy to use
- Strong and flexible bond with good gap filling properties

### CaberFix adhesives are available in

Product	Size	Format	Units per box
CaberFix D4	1 kg	Bottle	12
CaberFix D3	1 kg	Bottle	12
CaberFix Joint&Joist	310 ml	Cartridge	12
CaberFix Pro Kit†	50m <sup>2</sup>	Mix	1

† 1 x CaberFix D3, 7 x CaberFix Joint&Joist, 3 x CaberFix Tape



### Our CaberBoard range - flooring systems for domestic and commercial floors

- |                   |                        |                         |
|-------------------|------------------------|-------------------------|
| • CaberFloor P5   | <b>Adhesives</b>       | <b>Tapes</b>            |
| • CaberDek        | • CaberFix D4          | • CaberFix Tape         |
| • CaberShieldPlus | • CaberFix D3          | • CaberFix X-Treme Tape |
| • CaberAcoustic   | • CaberFix Joint&Joist |                         |

CaberFix Adhesives conform with:



\*\*When installed according to manufacturer's instructions

For more information on CaberBoard, call 01786 819 225  
or if you require technical advice call: 01786 819 449

[CaberBoard.com](http://CaberBoard.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

**CaberBoard®**  
Trusted flooring systems

## A range of tapes specifically developed for use with CaberDek flooring.

### CaberFix® X-Treme Tape

Highly durable and scuff resistant flooring joint tape formulated to withstand severe winter conditions.

- Bonds well in damp conditions and doesn't lift when wet
- Will work in conditions up to, and including, minus 21 degrees C
- High tack strength won't lift in tough working conditions
- Provides BBA approval for 42 days exposure when installed as part of the CaberFix sealing and fixing system\*



\* When installed according to manufacturer's instructions

### CaberFix® Tape

Polyethylene-coated cloth tape for sealing CaberDek flooring during construction phases.

- 100% waterproof for sealing exposed joints and perimeter edges
- Easy to tear and conform to irregular surfaces
- UV resistant for durability
- Provides BBA approval for 42 days exposure when installed as part of the CaberFix sealing and fixing system\*



Suitable for  CaberDek

Not sure which flooring or tape is right for the job? Visit our website to view our handy flowchart!



### CaberFix tapes are available in

Product	Size	Format	Units per box
CaberFix X-Treme Tape	48mm x 50m	Roll	12
CaberFix Tape	48mm x 50m	Roll	24
CaberFix Pro Kit <sup>†</sup>	50m <sup>2</sup>	Mix	1

<sup>†</sup> 1 x CaberFix D3, 7 x CaberFix Joint&Joist, 3 x CaberFix Tape

### Our CaberBoard range - flooring systems for domestic and commercial floors

- |                   |                        |                         |
|-------------------|------------------------|-------------------------|
| • CaberFloor P5   | <b>Adhesives</b>       | <b>Tapes</b>            |
| • CaberDek        | • CaberFix D4          | • CaberFix Tape         |
| • CaberShieldPlus | • CaberFix D3          | • CaberFix X-Treme Tape |
| • CaberAcoustic   | • CaberFix Joint&Joist |                         |

CaberFix Tapes conform with:



\*\* When installed according to manufacturer's instructions

For more information on CaberBoard, call 01786 819 225 or if you require technical advice call: 01786 819 449

[CaberBoard.com](http://CaberBoard.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

**CaberBoard®**  
Trusted flooring systems

High quality, lightweight MDF with enhanced smooth surface and consistent density.

- Enhanced surface gives a great finish – ideal for painting, paper foils and veneers
- Consistent density ensures it saws, drills, shapes and routs cleanly and easily
- Engineered from UK sourced wood and BS EN 622 parts 1 and 5 accredited

Best for use on

- Shop fitting
- Furniture
- Kitchen & bathroom joinery
- Exhibition displays
- General purpose joinery
- Caravan manufacture

Make the job easier with a product that saws, drills, shapes and routs cleanly and easily, without splintering or chipping.



### CaberWood MDF Trade is available\* in

Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
12	2440	1220	SE	60
12	3050	1220	SE	64
15	2440	1220	SE	56
15	3050	1220	SE	50
18	2440	1220	SE	48
18	3050	1220	SE	42
22	2440	1220	SE	32
22	3050	1220	SE	32
25	2440	1220	SE	35
25	3050	1220	SE	30

\*Minimum quantities and lead times may apply

### Our CaberWood MDF range - in a league of its own

- CaberWood MDF Trade
- CaberWood MDF Trade MR
- CaberWood MDF Pro
- CaberWood MDF Pro MR
- CaberWood MDF Industrial

CaberWood MDF conforms with:



For more information on CaberWood MDF, call 01786 819 225 or if you require technical advice call: 01786 819 449

[CaberWoodMDF.com](http://CaberWoodMDF.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

**CaberWood MDF®**  
Legendary performance

Join in the conversation @CaberWoodMDF

# CaberWood MDF® Trade MR

WE MAKE IT BETTER  
ACROSS THE BOARD

## Lightweight and moisture resistant board for general purpose joinery.

- Performs well in occasionally wet or humid environments
- High quality fibre and internal bond strength gives excellent holding of screws and fastenings
- Saws, drills, shapes and routs cleanly and easily
- No splintering or chipping

Best for use on

- Shop fitting
- Furniture
- Exhibition displays
- Kitchen & bathroom joinery/furniture
- Wood panelling
- Humid conditions

Performs well in occasional wet or humid environments, making it ideal for kitchen and bathroom furniture.



CaberWood MDF Trade MR is available\* in

Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
12	2440	1220	SE	60
12	3050	1220	SE	64
15	2440	1220	SE	56
15	3050	1220	SE	50
18	2440	1220	SE	48
18	3050	1220	SE	42
22	2440	1220	SE	32
25	2440	1220	SE	35
25	3050	1220	SE	30

\*Minimum quantities and lead times may apply

Our CaberWood MDF range - in a league of its own

- CaberWood MDF Trade
- CaberWood MDF Trade MR
- CaberWood MDF Pro
- CaberWood MDF Pro MR
- CaberWood MDF Industrial

CaberWood MDF conforms with:



For more information on CaberWood MDF, call 01786 819 225 or if you require technical advice call: 01786 819 449

[CaberWoodMDF.com](http://CaberWoodMDF.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

# CaberWood MDF®

Legendary performance

Join in the conversation  @CaberWoodMDF

A premium grade MDF with a consistent density for high quality finishing.

- Straight-forward machine and surface finishing
- Excellent holding of screws and fastenings
- Consistent density ensures cutting and routing need minimal finishing
- Saws and drills easily, shapes and routs cleanly

- Best for use on
- Shop fitting
  - General purpose joinery
  - Furniture
  - Wall panelling
  - Architectural mouldings
  - Door manufacture
  - Fire surrounds
  - Mouldings
  - Exhibition displays
  - Staircases

## CaberWood MDF Pro is available\* in

Panel Size (mm)	Sheets per pack per panel thickness (mm)										
	6	9	12	15	18	19	22	25	30	36	38
2440 x 1220	60	60	60	48	40	37	32	30	24	20	20
2440 x 1525	-	-	-	-	32	-	-	24	-	-	-
2440 x 1830	-	-	-	36	30	-	-	24	18	-	-
3050 x 1220	78	60	48	40	32	-	32	24	18	16	15
3660 x 1220	-	-	-	18	24	-	24	24	20	-	-

\*Minimum quantities and lead times may apply

## Our CaberWood MDF range - in a league of its own

- CaberWood MDF Trade
- CaberWood MDF Trade MR
- CaberWood MDF Pro
- CaberWood MDF Pro MR
- CaberWood MDF Industrial



CaberWood MDF conforms with:



For more information on CaberWood MDF, call 01786 819 225  
or if you require technical advice call: 01786 819 449

[CaberWoodMDF.com](http://CaberWoodMDF.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

 **CaberWood MDF®**  
Legendary performance

Join in the conversation  @CaberWoodMDF

# CaberWood MDF® Pro MR

WE MAKE IT BETTER  
ACROSS THE BOARD

Premium grade MDF that performs well in occasionally wet or humid environments.

- Consistent high density across the board allowing the most intricate edge profiling and surface routing
- Enhanced, smooth surface is ready for paint, paper foils and veneers
- High quality fibres and internal bond strength for superior holding of screws and fastenings

Suitable for use with all woodworking machines and hand tools, giving you complete flexibility.

Best for use on

- Wall panelling
- Caravan manufacture
- Window boards
- Kitchen and bathroom furniture
- General purpose joinery
- Architectural mouldings
- Doors
- Furniture
- Humid conditions



CaberWood MDF Pro MR is available\* in

Panel Size (mm)	Sheets per pack per panel thickness (mm)							
	6	9	12	15	18	22	25	30
2440 x 1220	60	60	60	48	40	32	30	24
3050 x 1220	78	60	48	40	32	32	24	18

\*Minimum quantities and lead times may apply

Our CaberWood MDF range - in a league of its own

- CaberWood MDF Trade
- CaberWood MDF Trade MR
- CaberWood MDF Pro
- CaberWood MDF Pro MR
- CaberWood MDF Industrial

CaberWood MDF conforms with:



For more information on CaberWood MDF, call 01786 819 225  
or if you require technical advice call: 01786 819 449

[CaberWoodMDF.com](http://CaberWoodMDF.com)



[www.norbord.co.uk](http://www.norbord.co.uk)

**CaberWood MDF®**  
Legendary performance

Join in the conversation @CaberWoodMDF

CaberWood MDF® Pro MR

# CaberWood MDF® Industrial

WE MAKE IT BETTER  
ACROSS THE BOARD

## Denser design for deep profiles and consistent performance.

- The ultimate MDF, ideal for advanced routing, allowing more complicated profiles to be cut.
- Suitable for use with all woodworking machines and hand tools
- High density design allows advanced finishing and deep, angular profiles
- Enhanced, smooth surface is ready for paint, paper foils and veneers
- Gives a superior routed finish

- Best for use on
- Shopfitting
  - Furniture
  - Fire surrounds
  - Architectural mouldings
  - Staircases
  - Wall panelling
  - Doors
  - Shelving
  - Wrap mouldings
  - General purpose joinery
  - Humid conditions
  - Chairs, tables, cabinets
  - Kitchen and bedroom furniture

CaberWood MDF Industrial is made to order. Please contact our product support team on: **01786 819 449**

### Our CaberWood MDF range - in a league of its own

- CaberWood MDF Trade
- CaberWood MDF Trade MR
- CaberWood MDF Pro
- CaberWood MDF Pro MR
- CaberWood MDF Industrial



CaberWood MDF conforms with:



For more information on CaberWood MDF, call **01786 819 225** or if you require technical advice call: **01786 819 449**

**CaberWoodMDF.com**



[www.norbord.co.uk](http://www.norbord.co.uk)

# CaberWood MDF®

Legendary performance

Join in the conversation  @CaberWoodMDF